





标记(Mark)	处数(No.)	更改文件号File change No.	更改内容(Content changed)	签名(Signature)	日期(Date)


Dimension: (Unit: mm)



Motor Connctions:



B+ 红 Red B- 蓝 Blue



柔性电缆线

Common Rating

Step angle	1.8°
Position accuracy	1.8±0.09°
Dielectric strength	500VAC 1min
Insulation resistance	100MOhm(500VDC)
Insulation class	B
Temp rise(Max)	80K
Radial play	Max.0.02mm(Load 450g)
Axial play	Max.0.08mm(Load 900g)

Specification:

Current/phase	1.5 A
Voltage	2.55 V
DC Resistance/phase ±10%	1.7 Ω
Inductance/phase ±20%	2.6 mH
Holding torque	0.15 N•M
Inertia	0.019kg•cm ²
Weight	0.21 kg

技术要求:
1、未注形位公差按GB/T 1184-K;
2、未注尺寸公差按GB/T 1804-m。
(除非另外指定)

设计 Designed		标准化 Standardized		材料(Material):	名称(Title)	步进电机
制图 Drawn					型号(Model)	35CM015-ZK MS20
校对 Proofread		审核 Checked		重量(Weight)/g:	图号(DWG No.)	LS-35CM015-ZK MS20
工艺 Processed		批准 Approved		阶段标记(Stage Mark)	料号(Part No.)	
表单编号 Form No.	LS-QP-46-09A	版本/版次 Edition/Serial NO.	A/01	共1页第1页 Page 1 of 1	比例(Scale)	1:1

